

WORKMASTER™ DIELECTRIC OVERBOOTS



RESPIREX™

Power Generation

Power Distribution

Construction

Telecommunications

Transport

An electrically insulating dielectric overboot approved to current European standards with a vulcanized rubber sole for superior slip resistance. The Respirex dielectric boot provides protection of up to 20kV over the complete boot for over three minutes.



17 kV
Maximum Working Voltage

Boot Shaft

- Ingenious rear entry design ensures the boot is quick and easy to fit and remove
- Ideal for personnel who have to continually enter and exit hazardous areas
- Yellow dielectric compound shaft
- Seamless construction
- Kick off lug
- REACH Compliant

Boot Sole

- Blue vulcanized rubber sole for maximum grip - 30% better than a conventional safety boot sole
- Slip resistance performance twice that required by EN 13287 SRA and SATRA TM144 standards
- Two to three times the wear resistance of conventional soles
- Fuel and oil resistant
- Greater cut resistance than conventional soles
- Resistance to hot contact 60 seconds 300°C.

Care

- Machine washable at up to 40°C
- Shelf life of over 10 years

Electrical Protection

Complete boot: 20 kV.....3 Minutes, no damage
5 kV.....Less than 5mA Leakage current

Certification

Safety Footwear	EN ISO 20347 I E HRO SRA FO
Electrically Insulating Footwear	EN 50321 Class 0
Dielectric Footwear	ASTM F1117
Personal Protective Equipment	PPE DIR 89/686/EEC

Sizes

	Medium	Large	Extra-Large
UK	6 - 8	9 - 11	12 - 14
EU	39 - 42	43 - 45	46 - 49
US	7 - 9	10 - 12	13 - 15

